



ITUX97

38.1cm(15.0 inch)UXGA(1600×1200)
Color TFT LCD Module



Highlight:

Features

- UXGA 1600×1200 pixels(1.92M pixels)
- 150cd/m² Typ. Brightness
- Native 262K colors(RGB 6-bit data driver)
- 317.3mm×242.0mm×6.7mm Typ./7.0 Max.
- Using the Post Spacer
- 2.44 times as many pixels as XGA(1024×768)

Applications

- Notebook PCs
- KIOSK Application
- Measuring Instrument




ITUX97 is a 38.1cm(15.0 inch) color TFT LCD module, and designed for a notebook style personal computer. The screen format and electrical interface are intended to support UXGA(1600 × 1200) screen. Support color is native 262K colors(RGB 6-bit data driver) All input signals are LVDS(Low Voltage Differential Signaling) interface compatible. Displaying beautiful pictures using the Post Spacer*.

*Post Spacer : Post Spacer is a new technology which keeps a gap between Color filter and TFT array using organic column instead of conventional spacer balls.

For more information about this product, please contact:
IBM Japan, Ltd.
LCD Marketing
Technology Market Development
1623-14, Shimotsuruma, Yamato-shi,
Kanagawa-ken 242-8502, Japan
Tel : 81-46-215-6551
Fax: 81-46-273-6975

Specifications

Screen Diagonal(mm)	381(15.0 inch)
Active Area(mm)	304.8(H) × 228.6(V)
Pixel H × V(pixels)	1600 × 1200
Pixel Pitch(mm)	0.1905(per one triad) × 0.1905
Pixel Arrangement	R.G.B. Vertical Stripe
Display Mode	Normally White
White Luminance(cd/m ²)	Center ~ 5 point average
Design Point 1 : (ICFL=3.5mA)	90 Typ. ~ 85 Typ.
Design Point 2 : (ICFL=6.5mA)	150 Typ. ~ 140 Typ.
Contrast Ratio	200 : 1 Typ.
Optical Rise Time/Fall Time(msec)	30 Typ. , 50 Max.
Nominal Input Voltage(volt @ VDD)	+3.3(+3.0 to +3.6)
Power Consumption(watt @ VDD line)	3.1 Typ.(TBD) , 3.6 Max.(TBD)
Lamp Power Consumption(watt)	(w/o inverter loss)
Design Point 1 : (ICFL=3.5mA)	2.7 Typ.(TBD)
Design Point 2 : (ICFL=6.5mA)	4.4 Typ.(TBD)
Weight(grams)	650 Typ.
Physical Size : W × H × D(mm)	317.3 × 242.0 × 6.7 Typ. / 7.0 Max.
Electrical Interface	8 pairs LVDS(Even/Odd R/G/B Data(6bit) , 3sync signals, Clock)
Support Color	Native 262K colors(RGB 6-bit data driver)
Temperature Range()	
Operating	0 to +50
Storage(Shipping)	-20 to +60



IBM is the trademark of International Business Machines Corporation in the United States and / or other countries.



IBM Japan, Ltd.

2-12, Roppongi 3-chome, Minato-ku, Tokyo 106-8711, Japan
10-00 Printed in Japan
© Copyright IBM Corporation 2000

Picture in this catalog may differ from actual products.
Specifications of products are subject to change without notice.
Display and printout data are not actual data.